

## **GTEK MINERAL TECHNOLOGIES**

Tel: +86-15958229409; +86-18602111147 Email: gtek@shaking-tables.com Web: www.mineral-technology.com

# **GTEK** Laboratory Spiral Chute



of high quality polyurethane with fiberglass banking and wearable corundum inner surface.

## Product Advantages

- 1. Reasonable structure and small occupation area
- 2. High recovery, high efficiency, and precise separation
- 3. Light in weight, rust and corrosion resistant
- 4. Simple installation and Minimal maintenance requirements
- 5. Low operating cost and long operating life
- 6. Reliable running with minimal operator attention
- 7. Strong adaptability to fluctuation of feeding amount, density, size and grade

### **Technical Specification**

Model		5LL-600	5LL-400
Outside Diameter (mm)		600	400
Pitch (mm)		450, 360, 270	240, 180
Pitch Diameter Ratio		0.75, 0.6, 0.45	0.6, 0.45
Lateral Slope		9°	9°
Maximum Starts per Column		3	2
Feeding Size (mm)		0.2-0.02	0.2-0.02
Feeding Density (%)		25-55	25-55
Capacity (t/hr)		0.8-1.2	0.15-0.2
External Size	Length (mm)	700	460
	Width (mm)	700	460
	Height (mm)	2600	1500
Weight (kg)		150	50